

RG Series REMOVEABLE GOOSENECK



GENERAL DATA SHEET - PART NUMBER RG-35

Model: RG-35 Hydraulic Detachable Gooseneck Trailer

Capacity: 70,000#

Trailer weight: 14,840# +/- 3%

Gross vehicle weight rating: 84,840#

DIMENSIONS

- Overall Length: 44' 3"
- Overall Width: 8' 6"
- Loadwell length: 22'
- Loadwell height: 25" unloaded

GOOSENECK STYLE & DIMENSIONS

- Style: 2 angle scraper GROUND BEARING
- Length: 11' 4"
- 5th wheel height: 50"
- Swing clearance: 90"
- Kingpin setting: 15"
- Kingpin size: 2"

HYDRAULIC SYSTEM

- Engine: 10 HP electric start
- Pump: 2 GPM
- Control valve: 2500 psi
- Cylinder: (1) 6" bore w/22" stroke

BED STRUCTURE W/TAPERED FRONT BEAM

- Main frame: W16x57 beams A992 grade 50
- Side beam: W12x22 A992 grade 50
- Cross members: W8x10 A992 full width
- Decking: 2" Oak lumber
- 12" cast iron outriggers, 12 each side

SUSPENSION

- Hutch #H9700TUS-49AC-UN/MT Spring and equalizer, #365-00 heavy duty 3 leaf spring

AXLES

- 2 Hendrickson 5" round 25,000# capacity w/Hub piloted wheels

RIMS & TIRES

- Unimount style 8.25" x 22.5"
- 255/70 R22.5 Radial Tires

BRAKE SYSTEM

- Meritor/Wabco "Easy Stop" #20 60 10 Tandem Axle
- 2S1M ABS system
- 16-1/2" x 7" air S cam w/automatic slack adjusters
- Type 30/30 brake chambers

LIGHT SYSTEM

- Sealed modular wire harness
- 12-volt rubber mounted seal beam lights
- Reflective tape

LASHING "D" RINGS

- 3 per side of deck
- 1 on trunion between tires

FINISH

- 1 coat rust inhibitive enamel primer
- 2 coats high performance water borne one part urethane
- Choice of 7 factory standard colors



Rugged Durability, Performance, Value.