

## RG Series REMOVEABLE GOOSENECK



### GENERAL DATA SHEET - PART NUMBER RG-60

Model: RG-60 Hydraulic Detachable Gooseneck Trailer

**Capacity:** 120,000#

**Trailer weight:** 20,800# +/- 3%

**Gross vehicle weight rating:** 140,800#

#### DIMENSIONS:

- Overall Length: 48' 3"
- Overall Width: 8' 6"
- Loadwell length: 22'
- Loadwell height: 25" unloaded

#### GOOSENECK STYLE & DIMENSIONS:

- Style: Scraper
- Length: 11' 4"
- 5th wheel height: 50"
- Swing clearance: 90"
- Kingpin setting: 15"
- Kingpin size: 2"

#### HYDRAULIC SYSTEM:

- Engine: 10 HP electric start
- Pump: 2 GPM
- Control valve: 2500 psi
- Cylinder: (2) 6" bore w/22" stroke

#### BED STRUCTURE W/TAPERED FRONT BEAM:

- Main frame: W16x100 beams A992 grade 50
- Side beam: W12x22 A992 grade 50
- Cross members: W8x10 A992 full width
- Decking: 2" Oak lumber
- 12" cast iron outriggers, 12 each side

#### SUSPENSION:

- Hutch #H9700TUS-49AC-UN/MT Spring and equalizer, #365-00 heavy duty 3 leaf spring

#### AXLES:

- 3 Hendrickson 5" round 25,000# capacity w/Hub piloted wheels

#### RIMS & TIRES:

- Unimount style 8.25" x 22.5"
- 255/70 R 22.5 Radial tires

#### BRAKE SYSTEM:

- 16-1/2" x 7" air S cam w/automatic slack adjusters
- Type 30 and Type 30/30 brake chambers

#### LIGHT SYSTEM:

- Sealed modular wire harness
- 12-volt rubber mounted seal beam lights
- Reflective tape

#### LASHING "D" RINGS:

- 3 per side of deck
- 1 on trunion between tires

#### FINISH:

- 1 coat rust inhibitive enamel primer
- 2 coats high performance water bourne one part urethane
- Choice of 7 factory standard colors



Rugged Durability, Performance, Value.