

Non-Ground Bearing Removable Gooseneck

The image contains two technical drawings of a standard trailer. The top drawing is a top-down view showing the layout of the deck and the placement of the axles. The bottom drawing is a side elevation view showing the profile of the trailer, including the front end, the main body, and the rear section with three axles. Dimensions are provided in both feet and inches, and meters.

Standard Trailer Dimensions

Top View Dimensions:

- Overall length: 47' 5" - (14.46m)
- Overall width: 8' 6" - (2.59m)
- Front section width: 47.5" - (1.21m)
- Deck material: Wood Decking

Side View Dimensions:

- Overall length: 50' 6" - (15.39m)
- Front section length: 11' 6" - (3.51m)
- Front section width: 15" - (0.38m)
- Front section height: 90" - (2.29m)
- Front section width at base: 50" - (1.27m)
- Front section width at top: 34" - (0.86m)
- Front section width at bottom: 24" - (7.32m)
- Front section width at rear: 15' - (4.57m)
- Front section width at rear: 40" - (1.02m)
- Front section width at rear: 9" - (0.23m)
- Front section width at rear: 25" - (0.64m)
- Front section width at rear: 50" - (1.27m)
- Front section width at rear: 50" - (1.27m)
- Overall width: 42' 7" - (12.98m)

GVWR	
Axle, Suspension, & Running Gear	
# of Axles	3 Air Suspension Axles
Axle Spacing	49"
Axle Capacity	22,500 lbs.
Brakes	16 ½" x 7" – 22,500 lbs.
ABS	Optional
Decking / Flooring	
Main Decking	2" Oak Lumber (Open Center)
Wheel Assembly	
Tires	255 / 70R x 22.5
Rims	8.25 x 22.5 Steel Wheels
Finish	
Anticorrosive Undercoat – 2 Coats Epoxy Primer	
2 Coats Gloss Acrylic Enamel Top Coat	
Mud Flaps & Reflective Tape	
Popular Options	
Additional Deck Length up to 28'	
Additional Axles	
Aluminum Wheels	
Apitong Wood Decking	
Beavertail w/ Ramps	
Bucketwell	
Combo Wet Line Power System	
Covered Wheels (Welded or Removable)	
Flush Bed Hooks	
T-1 100ksi (Main Frame)	

2700 S Tamiami Trail Suite 9, Sarasota FL. 34239
www.sitrade.biz Tel USA +1 941 441 6751 - sales@sitrade.biz