




Model: RG - 52

Ground Bearing Removable Gooseneck

Overall Length	Overall Width	Gooseneck Length	Deck Length	Deck Height	Tail Length	Tail Height	Ground Clearance
48' 6"	8' 6"	11' 6"	22'	25"	15'	40"	9"



Weight 18,540 lbs. Capacity 104,000 lbs.

GVWR 122,540 lbs.

Gooseneck	
King Pin Style	Fixed
King Pin Setting	15"
Swing Clearance	90"
5 th Wheel Height	50"
King Pin	2"
Ride Height Adj.	N/A

Axle, Suspension, & Running Gear	
# of Axles	3 Spring Suspension Axles
Axle Spacing	49"
Axle Capacity	25,000 lbs.
Brakes	16 1/2" x 7" - 25,000 lbs.
ABS	Optional

Main Deck	
Main Beam	W16x77 Beams A992 Grade 50
Centers	40" Standard
Side Beams	W12x22 A992 Grade 50
Crossmembers	W8x10 A992 Grade 50
Spacing	24" Standard
Outriggers	12" Cast Iron, 12 Each Side
# of D-Rings	3 per Side
Front Ramps	Optional
Concentrated Load	104,000 lbs. (Within a 16' Span)

Decking / Flooring	
Main Decking	2" Oak Lumber (Open Center)

Tail Section	
Riser	30°

Wheel Assembly	
Tires	255/ 70R 22.5
Rims	8.25 x 22.5 Steel Wheels

Electrical	
Lights	Sealed Modular Wire Harness
Connector	7 Way Connector

Finish	
Anticorrosive Undercoat - 2 Coats Epoxy Primer	
2 Coats Gloss Acrylic Enamel Top Coat	
Mud Flaps & Reflective Tape	

Hydraulics	
Cylinder (1)	8" Bore w/ 22" Stroke
Control Valve	2,500 psi
Engine: 10 HP Electrical Start - Pump: 1 GPM	

Popular Options	
13 Horse Power Motor	
Air Ride Suspension w/ Lift Axle	
Aluminum Wheels	
Apitong Wood Decking	
Beavertail w/ Ramps	
Bucketwell	
Combo Wet Line & Power System	
Covered Wheels (Welded or Removable)	
Flush Bed Hooks	
T-1 100ksi (Main Frame)	